

nola®

Nola > Products > Island – New Product!



Island – New Product! Furniture group

DESIGN FÄRG & BLANCHE

The Island furniture group challenges the traditional and rectangular bench table with its organic and asymmetrical shapes. Tables and benches with varying widths on the sides bring out a sense of playfulness in the arrangement while inviting people to sit in various ways. By placing multiple tables lengthwise, seating arrangements can be created where everyone can see each other.

The furniture is crafted from wood and hot-dip galvanized steel and can be purchased individually, with or without armrests on the sofa and bench, as well as in groups. The pieces are cast or bolted to the ground.

Dimensions and weight**Island Bench**

Length: 165 cm

Height: 64,5 cm

Armrest height: 18,5 cm

Sitting height: 46 cm

Depth: 37,5 cm

Vikt: 18,5 kg

Island Backed bench

Width: 165 cm

Height: 78,5 cm

Armrest height: 18,5 cm

Sitting height: 46 cm

Depth: 53 cm

Vikt: 31,5 kg

Island Table

Length: 159 cm

Width: 79 cm

Height: 75 cm

Vikt: 29 kg

Island Picnic table

Length: 171 cm

Width: 214 cm

Height: 78,5 cm

Armrest height: 18,5 cm

Sitting height: 46 cm

Vikt: 80 kg

Product numbers and combinations**U17-50**

Island Bench

U17-51Island backed
bench with
armrests**U17-52**

Island Table

U17-53SBIsland Picnic table,
with a backed
bench, a bench
and a table.**U17-53SS**Island Picnic table,
with two backed

U17-53BB benches.
Island Picnic table,
with two benches.

Append to product number

WOOD AND FINISH

EK for oiled oak.

METAL SURFACE FINISH

RAL 7022

C for any color other than standard,
starting cost is added.

INSTALLATION TYPE

M for in-ground.

N for surface mount.

Standard colours

RAL 7022

Oljad ek

Materials and surface treatments

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if

left untreated and must therefore be surface treated. This is done through electro-galvanization and powder coating, hot-dip galvanizing, or application of a zinc powder primer.

Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

In-ground

Cast in ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance

can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

Powdercoated steel

Products that are electro-galvanized and powder-coated can be touch-up painted with alkyd paint.

Download our general maintenance advice

Versions

Available as backed bench, bench and table. Also available as a picnic table with a bench on one side of the table and a backed bench on the other. Bench and backed bench is available with or without armrests.

Sign up for our newsletter

Send



Contact

Head Office Stockholm

Nola Industrier AB
Box 17701
Repslagargatan 15b
118 93 Stockholm
Tel: 08-702 1960
Fax: 08-702 1962
headoffice@nola.se

Sales Office / Showroom Malmö

Nola Industrier AB
Neptunigatan 74
211 18 Malmö
Tel: 040 171 190



Nola Industrier AB
Highest credit worthiness
© Bisnode 2022