


# nola®



## Kebne Outdoor Gym Fitness Unit 1

KAUPPI & KAUPPI

The Kebne outdoor gym consists of five free-standing fitness units for strength training and stretching. Each of the five modules is designed for exercises that use the individual's own body weight as a counterweight for resistance training.

Fitness Unit 1 is designed primarily for back and bicep training. It is optimised for individuals taller than 1.75 cm but can accommodate other heights too. This unit has a lower side bar, enabling stronger people to get more out of the exercises they perform.

Kebne is developed in accordance with standard EN 16630 and meets its requirements for strength, calculated by independent party Structural Engineering AB with FEM-Design 3D Structure.

BIM models are available for this fitness unit.

For more detailed information, please see the *Kebne Brochure*


Follow Kebne on *Instagram*

Certifieringar



Produkt listad i  
Svanens Husportal

Utmärkelser



Dimensions and weight

Module: 1 Length: 210 cm Width: 140 cm  
 Height: 240 cm Fall height: 240 cm  
 Weight: 1.43 kg

Materials

Powder coated Steel RAL / Sablé.

Electro-plated powdercoated 38 x 2,5 mm steel pipe. Accoya® wood.

Standard colours

RAL 7016

RAL 1023

RAL 3009

Product number

Ö72-10

Kebne unit 1

Ö72-16N

Attachment mountings 4 pcs/ set, ABOVE ground level

Ö72-16M

Attachment mountings 4 pcs/ set, BELOW ground level

Ö72-SIGN 1

Signprint for unit 1

Ö72-15

Sign with metal plate

### **Additional description number**

GR for grey RAL 7016 antracit

GUL for yellow RAL 1023

VR for red RAL 3009

C for any colour, start up fee.

M for ground mounted, to foundation  
200 mm below ground.

N för attachable, mounted to foundation  
in ground level.

---

### **Assembly and placement**

Knock down system.

Bolts to the ground with screws (not  
included in the delivery).

When assembled and fixed into the  
ground (need to be mounted to  
foundation 20 cm under ground or  
above ground).

Fall height unit 1: 140cm

The frames can be attached to almost  
any surface material or cast in concrete,  
with room for a layer of cushioning to be  
added underneath. When assembled  
and fixed into the ground (need to be  
mounted to foundation 20 cm under  
ground).

---

### **Maintenance**

Repainted as needed.

**Download our general maintenance  
advice**

---

### **Variants**

Five models Height: 45-240 cm.

Standard colors: Gray RAL 7016 antracit,  
Yellow RAL 1023 och red RAL 3009.

---





Sign up for our newsletter

Send



---

Contact

Head Office Stockholm

Nola Industrier AB  
Box 17701  
Repslagargatan 15b  
118 93 Stockholm  
Tel: 08-702 1960  
Fax: 08-702 1962  
[headoffice@nola.se](mailto:headoffice@nola.se)

Sales Office / Showroom Malmö

Nola Industrier AB  
Skeppsbron 3  
211 20 Malmö  
Tel: 040 171 190