



Kebne Outdoor Gym Fitness Unit 5

KAUPPI & KAUPPI

The Kebne outdoor gym consists of five free-standing fitness units for strength training and stretching. The fitness units are designed for exercises that use the individual's own body weight as a counterweight for resistance training.

Fitness Unit 5 is designed primarily for leg training and abdominal exercises. The wooden surface is positioned at seat height, creating scope for it to be used as a bench.



Kebne is developed in accordance with standard EN 16630 and meets its requirements for strength, calculated by independent party Structural Engineering AB with FEM-Design 3D Structure.

BIM models are available for this fitness unit.

For more detailed information, please see the *Kebne Brochure*

Follow Kebne on *Instagram*

Utmärkelser



Dimensions and weight

Module 5

Length: 210 cm

Width: 140 cm

Height: 45 cm

Fall height: 45 cm

Weight: 74 kg

Materials

Accoya®.

Powder coated Steel RAL / Sablé.

Electro-plated powdercoated 38 x 2,5 mm steel pipe. Accoya® wood.

Standard colours

RAL 7016

RAL 1023

RAL 3009

Product number

Ö72-14
Ä72-14

Kebne module 5

Ä72-14

| | |
|-------------------|-----------------------------------------------------|
| Ö72-16N | Attachment mountings 4 pcs/ set, ABOVE ground level |
| Ö72-16M | Attachment mountings 4 pcs/ set, BELOW ground level |
| Ö72-SIGN | Sign with metal plate |
| Ö72-SIGN 5 | Signprint for module 5 |

Additional description number

GR for grey RAL 7016 antracit

GUL for yellow RAL 1023

VR for red RAL 3009

C for any colour, start up fee.

M for ground mounted, to foundation 200 mm below ground.

N för attachable, mounted to foundation in ground level.

Assembly and placement

Knock down system.

Bolts to the ground with screws (not included in the delivery).

When assembled and fixed into the ground (need to be mounted to foundation 20 cm under ground or above ground).

Fall height unit 5: 45cm

The frames can be attached to almost any surface material or cast in concrete, with room for a layer of cushioning to be added underneath. When assembled and fixed into the ground (need to be mounted to foundation 20 cm under ground).

Maintenance

Repainted as needed.

Download our general maintenance
advice

Variants

Five models Height: 45-240 cm.
Standard colors: Gray RAL 7016 antracit,
Yellow RAL 1023 och red RAL 3009.









Sign up for our newsletter

Send



Contact

Head Office Stockholm

Nola Industrier AB
Box 17701
Repslagargatan 15b
118 93 Stockholm
Tel: 08-702 1960
Fax: 08-702 1962
headoffice@nola.se

Sales Office / Showroom Malmö

Nola Industrier AB
Skeppsbron 3
211 20 Malmö
Tel: 040 171 190