



# OSAKA Planter



Square High  
530L



Square Low  
240L



Rhombus High  
450L



Rhombus Low  
220L







## Color



INDOOR



OUTDOOR






## DETAIL



Articulated Feet

## CONFIGURATION EXAMPLES







- Planters available in two shapes: Square and Rhombus
- Four capacities and shapes:
  - Square high. Height 850 mm (530 L).
  - Square low. Height 420 mm (240 L).
  - Rhombus high. Height 850 mm (450 L).
  - Rhombus low. Height 420 mm (220 L).
- Modularity: can be installed individually or combined with each other and with the Osaka bench, creating green and rest areas, with an infinite number of possible configurations.
- The planters incorporate drainage holes in the base.
- Planters incorporate adjustable articulated feet.
- Planters can be anchored to the ground using 4 M8 expansion screws (included).
- Made of 1'5, 2 and 3 mm galvanized steel and finished with a thermo-heating polyester powder coated finish with a zinc-rich anti-corrosion primer in decorative frame.
- Guaranteed reliability: this product has satisfactorily exceeded functionality and endurance tests under real environmental and usage conditions.
- Suitable to be used indoor and outdoor under normal weather conditions. In case of extreme weather conditions, such as high salinity, temperature or humidity, an additional special treatment can be included. Check extra cost and MOQ.



## REFERENCE FOR OSAKA PLANTER

To process all your order, you must choose the corresponding model code.

### MODEL CODE

Code		Description
MPCU811		Osaka Planter square high (530L)
MPCU812		Osaka Planter square low (240L)
MPCU813		Osaka Planter rhombus high (450L)
MPCU814		Osaka Planter rhombus low (220L)


### EXTRA FINISHES (TO IMPROVE CORROSION RESISTANCE)

Reference	Extra Finishes	Description
<b>XT</b>	*Extreme finishing	Additional Extreme Treatment Anticorrosive Primer Zinc Rich (for products made from galvanized steel) That meets the requirements of a corrosion class C5 I according to DIN EN ISO 12944

\*Depends on request. MOQ required

## PACKAGING-LOGISTIC DETAILS

### Packaging details with pallet



Description	u. / pallet	Type of Packing	Pallet dimensions mm*			Pallet Weight	Volume
			Large	Width	Height		
Osaka Planter rhombus low	4	shrink wrapped	1200	800	1750	148 Kg	1,68 m <sup>3</sup>
Osaka Planter rhombus high	2	shrink wrapped	1200	800	1800	120 Kg	1,73 m <sup>3</sup>
Osaka Planter square low	4	shrink wrapped	1200	1000	1750	155 Kg	2,10 m <sup>3</sup>
Osaka Planter square high	2	shrink wrapped	1200	1000	1800	125 Kg	2,16 m <sup>3</sup>

\*Could be changed to make easy the logistic optimization in case of mixed items  
Ask for logistic optimization for full containers, trailers or trucks