TECHNICAL SPECIFICATION

El Poeta Bench

ALFREDO HÄBERLI 2005





COMPONENTS, MATERIALS and FINISHES:

LEGS in Ø25x2mm cold-rolled steel tube.

SEAT in Ø25x2mm cold-rolled steel tube chassis, covered with perforated steel sheet of 2mm thickness. Standard perforated (Flowers) or basic perforated (Basic), or optionals perforated (Stars and Points). Legs and seat with a cataphoresis covering painted with polyester resin without TGIC in bronce ADAPTA ref. 06-14453-RX / 2 or silver grey texturized ROHM IHAAS ref. 422 02 03610 - 10171197. Both colours are metalized.

M-8 stainless steel SCREWS with safety nut.

DIMENSIONS and WEIGHTS:

-The Poet: 1800 x 840 x H.740mm (H. Seat: 410mm) / 36Kg The placement of the screw for assembling is Ø8mm.

INTALLATION:

The benches must always be properly screwed to the floor. Screws are not supplied by BD.

PACKAGING:


The legs and seats are delivered packaged on pallets, protected by cardboard and plastic corner guards. The benches will be supplied unassembled.

TESTS:

The benches are certified based on the UNE-EN standard 12727:01 FUR-NITURE. ALIGNED SEATS, in 4 level, severe public use.

The horizontal tables based on the ISO/DIS standard 8019:86 "TABLES. RESISTANCE AND DURABILITY", in 5 level, severe public use. Salt spray corrosion tests (500 hours) for the painting process.

THE STANDARD POET



PERFORATED SHEET



MEASUREMENTS IN MM



JPDATED: 06/06/2019

Technical Department

Carretera Capellades / km 22,750 Narcís Monturiol, 7 / Pol. Ind Sesrovires Sant Esteve de Sesrovires / 08635 Barcelona Tel +34 93 771 30 51 / Fax +34 93 771 32 32